



MEDIUM INTENSITY STROBE FAA-L-865	MEDIUM INTENSITY DUAL STROBE/LED FAA L-864/865
<b>STL-1, STL-3 Specifications</b>	<b>STLD-1, STLD-3 Specifications</b>
<b>Protection:</b> MOV's, isolation transformer	<b>Protection:</b> MOV's, isolation transformer
<b>Alarms:</b> Form "C", power fail, pec fail, strobe fail	<b>Alarms:</b> Form "C", power fail, pec fail, strobe/beacon fail
<b>Warranty:</b> 2 year limited warranty	<b>Warranty:</b> 2 year limited warranty
<b>FAA Compliance:</b> AC-150/5345-43F	<b>FAA Compliance:</b> AC-150/5345-43F
<b>Applications:</b> Towers, chimneys, buildings, other structures	<b>Applications:</b> Towers, chimneys, buildings, other structures
<b>Enclosure:</b> NEMA 4x fiberglass	<b>Enclosure:</b> NEMA 4x fiberglass
<b>Dimensions (HxWxL):</b> STL-1 – 19.9"x17.25"x9.75" (457mm x 406mm x 235mm), STL-3 – 29.5"x19.68"x11.81" (750mm x 500mm x 300mm)	<b>Dimensions (HxWxL):</b> STLD-1 – 19.9"x17.25"x9.75" (457mm x 406mm x 235mm), STLD-3 – 29.5"x19.68"x11.81" (750mm x 500mm x 300mm)
<b>Weight:</b> STL-1 – 45lbs (20.4kg), STL-3 – 100lbs (46.5kg)	<b>Weight:</b> STLD-1 – 55lbs (24.95kg), STLD-3 – 110lbs (50.5kg)
<b>STL Cable (Diameter / Weight per 100ft.):</b> 0.625" +/-10% / 24lbs (15.9mm +/- 10% / 19.9kg)	<b>STLD Cable (Diameter / Weight per 100ft.):</b> 0.625" +/-10% / 24lbs (15.9mm +/- 10% / 19.9kg)

RB-LED/RB-300 RED BEACON TYPE FAA-L-864	SL-1LED / SL-2LED AND SL-1 / SL-2 OBSTRUCTION LIGHT FAA-L-810
<b>RL-1SS:</b> Unalarmed controller for 1 beacon and up to 12 obstruction lamps.	<b>RL-0:</b> Unalarmed controller for 2 to 9 obstruction lamps.
<b>RL-1M:</b> Alarmed controller for 1 beacon and up to 4 obstruction lamps.	<b>RL-0M:</b> Alarmed controller for 2 to 9 obstruction lamps.
<b>RL-3SSB:</b> Unalarmed controller for 3 beacons and up to 12 obstruction lamps.	<b>RL-0WF:</b> Unalarmed flashing controller for 2 to 9 obstruction lamps.
<b>RL-3MB:</b> Alarmed controller for 3 beacons and up to 8 obstruction lamps.	

<p><b>Services:</b> Technical support 24/365, system installation and maintenance contracts.</p> <p>Other controllers available depending on the particular applications</p> <p>Modular construction for ease of service and maintenance</p>	<p><b>FOR MORE INFORMATION PLEASE CONTACT SPECIALTY TOWER LIGHTING</b></p> <p>1630 ELMVIEW DR. HOUSTON, TX 77080 TEL. 713-722-8123 FAX713-722-8744</p>
--	--