



SL-1 SPECIFICATIONS FAA-L-810 SINGLE OBSTRUCTION LIGHT

Intensity	Low
Horizontal Coverage	360°
Vertical Beam	10° Minimum
Lamp Description	116A21TS, 8000 Hours Life
Effective Candelas	32.5 Minimum
Height	7.5"
Diameter	4.875"
Fixture Base Material	Aluminum A-356
Lens Material	Pyrex Glass
Voltage	120VAC 60 HZ (Available in other voltages)
Wattage	116 Watts
Weight	3 lbs.
Operating Temperature	-55 C° to +55 C°
Wind Load	CAAA= 0.2 FT2
Hardware Material	Stainless Steel
Lamp Holder	Ceramic

QUALITY:

- Resistant to heavy rain or storms and corrosion.
- Resistant to shock and vibration.

ADVANTAGES:

- ETL certified to FAA (AC-150/5345-43F)
- 2 year warranty (excluding bulb).
- Applications: Towers, chimneys, bridges, buildings and other structures.
- Aluminum Base (no plastic).
- Price includes bulbs.

IMPORTANT:

- This fixture has (2) options of mounting (side and bottom hub) allowing the customer to choose a mounting preference without alerting the fixture.
- Technical service available 24/365.
- The use of non-OEM parts will void warranty.