



SL-2LED SPECIFICATIONS FAA-810 LED DOUBLE OBSTRUCTION LIGHT

Intensity	Low
Horizontal Coverage	360°
Vertical Beam	10° Minimum
Lamp Description	(2) 2 Luxeon Star LED
Effective Candelas	65 Minimum
Height	7.5"
Diameter	4.875"
Length	11"
Fixture Base Material	Aluminum A-356
LED Housing Material	Powder Coated Aluminum (red) and Glass
Voltage	120VAC 60 HZ (Available in other voltages)
Wattage	16 Watts
Weight	7 lbs.
Operating Temperature	-55 C° to +55 C°
Wind Load	CAAA= 0.2 FT2
Mounting Holes	0.75", 1", or 1.25" NPT (bottom hub)
Hardware Material	Stainless Steel

QUALITY:

- No preventive maintenance required after proper installation.
- Resistant to heavy rain or storms and corrosion.
- Resistant to shock and vibration.

ADVANTAGES:

- 95% less power consumption than incandescent light.
- 50 times more life compared to incandescent light.
- ETL certified to FAA (AC-150/5345-43F)
- 5 year warranty.
- Direct replacement for existing incandescent sidelights.
- Aluminum Base (no plastic).

IMPORTANT:

- Technical service available 24/365.
- The use of non-OEM parts will void warranty.