



### STLB-1 SPECIFICATIONS FAA-L-865 MEDIUM INTENSITY STROBE

Intensity	Medium
Horizontal Coverage	360°
Vertical Beam	3° Minimum
Lamp Description	Xenon Tube
Effective Candelas (Day Mode)	20,000 Nominal
Effective Candelas (Night Mode)	2,000 Nominal
Flashes Per Minute (Day Mode)	40 ± 2 Per minute
Flashes Per Minute (Night Mode)	40 ± 2 Per minute
Height	20-1/2"
Diameter	17"
Flashhead Base Material	Powder Coated Aluminum (Black)
Lens Material	Acrylic
Voltage	120VAC 60 HZ (Available in other voltages)
Wattage (Day Mode)	90 Watts
Wattage (Night Mode)	30 Watts
Weight	19 lbs.
Operating Temperature	-55 C° to +55 C°
Wind Load	CAAA= 1.5 FT2
Mounting Holes	Four mounting holes 11/16" spaced 90° on a 13.25" bolt circle
Hardware Material	Stainless Steel

#### QUALITY:

---

- Resistant to heavy rain or storms and corrosion.
- Resistant to shock and vibration.

#### ADVANTAGES:

---

- Low consumption of energy.
- ETL certified to FAA (AC-150/5345-43F)
- 2 year warranty.
- Applications: Towers, chimneys, bridges, buildings and other structures.
- Price includes Xenon tube.

#### IMPORTANT:

---

- This fixture is designed to be used with the controller STL-1.
- Technical service available 24/365.
- The use of non-OEM parts will void warranty.